




- obudowa i klosz wykonane z tworzywa uderzenioodpornego
- ten sam strumień świetlny przy 50% mniejszym zużyciu prądu (36W SMD LED=72W świetlówka kompaktowa)
- szeroki kąt świecenia lampy - 120 stopni
- klosz matowy
- źródło światła - dioda SMD LED
- ilość diod - 462 szt.
- moc 36 W
- wielopozycyjne ramię
- przewód H07RN-F 3x1,5mm² o długości 5m
- w opcji gniazda wbudowane w tylnej części lampy

- diffuser and casing made of impact resistant material
- the same light stream at 50% less power consumption (36W SMD LED = 72W compact fluorescent tube)
- wide angle of lighting - 120 degrees
- mat diffuser
- light source - SMD LED
- quantity of LEDs - 462 pcs
- power: 36W
- multi positional arm
- 5m rubber H07RN-F 3x1,5mm² cable
- socket at the back of the fitting as an option



~230V / LED / IP54, IP44 / IK10 / 1 szt. / 5m / 3,16 kg

nr kat. cat. no.	oprawa fitting	IP	gniazdo socket	rodzaj wtyczki plug type	kl. ochronności protection class	wyłącznik switch
293030	Taurus LED SMD 230V	IP54	-	UNI-SCHUKO	I	-
293061	Taurus LED SMD 230V	IP44	-	DK	I	-
293054	Taurus LED SMD 230V	IP54	PL-FR	UNI-SCHUKO	I	-
293047	Taurus LED SMD 230V	IP44	DK	DK	I	-
293016	Taurus LED SMD 230V	IP54	SCHUKO	UNI-SCHUKO	I	-
291524	Taurus LED SMD 230V	IP54	-	UNI-SCHUKO	I	+
291531	Taurus LED SMD 230V	IP44	-	DK	I	+
291548	Taurus LED SMD 230V	IP54	PL-FR	UNI-SCHUKO	I	+
291555	Taurus LED SMD 230V	IP44	DK	DK	I	+
291500	Taurus LED SMD 230V	IP54	SCHUKO	UNI-SCHUKO	I	+