

Recessed louvre fittings for TC-L lamps



ITCL336AL

Body:

White painted (RAL 9003) metal sheet

Optic (&):

ALDP - double parabolic louvre category

C2 of highly polished aluminium

MATDP - double parabolic louvre

category C2 of mat aluminium

AL - parabolic louvre of high polished aluminium with mat aluminium cross blades

ALMAT - parabolic louvre of mat aluminium

B - white parabolic louvre

Wiring (#):

compensated, ballast cat. B (standard)

EP - high frequency ballast HFB

EPSA - HFB analogue dimmable (1-10 V)

EPSD - HFB digital dimmable TRIDONIC ECO

EPSDD - HFB digital dimmable DALI

Application:

Recessed light fitting for installation into

false ceiling with visible supporting

structure (600x600/625x625 modules)

or gypsum plasterboard.

Accessories:

Fixing clips for installation into gypsum plasterboard – 54214.

Reduction frame for installing light fitting module 600 into false ceiling module 625.

Versions:

600 - for 600 module

ISO - external connection board ISODOM


KIT - external connection board BJB


K - with WIELAND connector

F - with flexible cord

OK - double-circuit wiring

For more info see pages 24-25.



Typ	W	Modul 600			kg
		A	B		
ITCL236 &#@	2x36 TC-L	596	596	576X576	3,8
ITCL336 &#@	3x36 TC-L	596	596	576x576	6,0

