

ACQUEX

Zone 2, 22.



IP66 explosionproof luminaire specially designed to be used in hazardous areas where an explosive atmosphere persists for a short period.



- Suitable for lighting premises of oil and gas, pharmaceutical, chemical, food and other industrial sites



IP66 Class I IK08 850°C -20°C to 40°C

ATEX Directive
94/9 EC

MATERIAL

Housing: Compressed glass fibre reinforced polyester in yellow (RAL 1003)
 Diffuser: Transparent polycarbonate
 Gear tray: White laquered steel plate
 Clips: Stainless Steel
 Gasket: Polyurethane
 One wire entry of \varnothing 20.5 mm

**MOUNTING ACCESSORIES**

Stainless steel fixing springs included



OPTIONS

- Emergency kit 1h or 3h




ACCESSORIES *(must be ordered separately)*




- Polyamide ATEX cable gland M20x1.5 IP66 for cable range \varnothing 6-13 (10115833)
- Brass nickel plated ATEX cable gland M20x1.5 IP66 for cable range \varnothing 6-13 (10115832)

Rated voltage: 220-240V / 0-50/60Hz

 II 3 G Ex nA IIC T6 Gc
 II 3 D Ex t IIIC T85°C Dc IP66

TECHNICAL FEATURES

Description	Code	L	D		 L x W x H (mm)	 euro	 KG
T5							
ACQUEX 2-114 E PC INOX	10107923	665	390	1	670x155x75	210	2.00
ACQUEX 2-124 E PC INOX	10107924	665	390	1	670x155x75	210	2.00
ACQUEX 2-128 E PC INOX	10107926	1282	800	1	1287x155x75	105	3.30
ACQUEX 2-154 E PC INOX	10107927	1282	800	1	1287x155x75	105	3.30
ACQUEX 2-135 E PC INOX	10107928	1578	1100	1	1587x155x75	105	3.95
ACQUEX 2-149 E PC INOX	10107929	1578	1100	1	1587x155x75	105	3.95
ACQUEX 2-180 E PC INOX	10114866	1578	1100	1	1587x155x75	105	3.95
ACQUEX 214 E PC INOX	10107933	665	390	1	670x155x75	210	2.00
ACQUEX 224 E PC INOX	10107934	665	390	1	670x155x75	210	2.00
ACQUEX 228 E PC INOX	10107936	1282	800	1	1287x155x75	105	3.30
ACQUEX 254 E PC INOX	10107937	1282	800	1	1287x155x75	105	3.30
ACQUEX 235 E PC INOX	10108176	1578	1100	1	1587x155x75	105	4.00
ACQUEX 249 E PC INOX	10107930	1578	1100	1	1587x155x75	105	4.00
T8							
ACQUEX 2-118 E PC INOX	10107925	665	390	1	670x155x75	210	2.00
ACQUEX 2-136 E PC INOX	10107931	1282	800	1	1287x155x75	105	3.30
ACQUEX 2-158 E PC INOX	10107932	1578	1100	1	1587x155x75	105	3.95
ACQUEX 218 E PC INOX	10107935	665	390	1	670x155x75	210	2.00
ACQUEX 236 E PC INOX	10107904	1282	800	1	1287x155x75	105	3.30
ACQUEX 258 E PC INOX	10107938	1578	1100	1	1587x155x75	105	3.95



ACQUEX 2x54W