Keine Kompromisse bei der Sicherheit !

Made in Germany

Datenblatt / Datasheet



AccuLux EX SLE 15/16 LED



EX-geschützte Arbeitsleuchte

mit Notlichtfunktion, in Fahrzeugen oder Gebäuden montierbar.

EX-proof working lamp

with emergency function, for installation in vehicles or buildings.

Zone 1, 2, 21, 22 Explosion protection ATEX: Ex II 2G Ex ib IIC T4 Gb / II 2D Ex ib IIIC T 135°C Db

Merkmale:

- ATEX-zertifiziert
- EX-geschützte Zonen 1, 2, 21, 22 (alle Gase + Stäube)
- 110° schwenkbarer Leuchtenkopf
- Abklappbarer Leuchtengriff
- Blei-Gel Akku (4V, 3,5 Ah)
- Gesichert gegen Tiefentladung
- Mit Notlichtfunktion (NLF*)
  (schaltet sich bei Stromausfall ein)
- 3 Schaltstufen: 2 Leuchtstufen + Blinkmodus
- Einsetzbar als Warnleuchte durch versch. Farbscheiben
- Staubdicht und spritzwassergeschützt
- Lichtstrom: ca. 180 Lumen (3W Power LED)
- Leuchtdauer: ca. 5 h / 75 h - Ladezeit: 4h
- Schutzart: IP 64
- Leuchtweite: ca. 170 m
- Gewicht: ca. 1100 g
- Maße in mm (Set): 104 x 245 x 120
- EX SLE 15 LED: ohne Linsenfokus
- EX SLE 16 LED: mit Linsenfokus
- LED-Kapazitätsanzeige

Features:

- ATEX certified
- EX-proof zones 1, 2, 21, 22 (all gases + dusts)
- 110° swivelling lamp head
- Removable lamp handle
- Lead gel accu (4V / 3,5 Ah)
- Protection against total discharge
- With emergency light function (ELF*)
  (turns on in case of power failure)
- 3 step switch: 2 steps for brightness + flash function
- Usable as warning lamp through diff. color discs
- Dustproof and splash-proof
- Luminous flux: ca 180 lumens (3W Power LED)
- Operating time: ca. 5 h / 75 h - Charging time: 4h
- Protection class: IP 64
- Range: up to ca. 170 m
- Weight: ca. 1100 g
- Dimensions in mm (Set): 104 x 245 x 120
- EX SLE 15 LED: no focus
- EX SLE 16 LED: focused light beam
- LED Capacity display



EX SLE 15 LED Leuchte

EX SLE 15 LED lamp

Art.Nr. 457831s



EX SLE 16 LED Leuchte

EX SLE 16 LED lamp

Art.Nr. 457832s



Ladestation LE 15

Charging station LE 15

Art.Nr. 457881n
(mit NLF / with ELF)*
Art.Nr. 457882n
(keine NLF / no ELF)*



EX SLE 15 LED Set mit Ladestation 12-24 V + 230 V und Farbscheiben
EX SLE 15 LED Set with charging station 12-24 V + 230 V and colour discs
Art.Nr. 457081s
(mit NLF / with ELF)*
Art.Nr. 457083s
(keine NLF / no ELF)*



EX SLE 16 LED Set mit Ladestation 12-24 V + 230 V und Farbscheiben
EX SLE 16 LED Set with charging station 12-24 V + 230 V and colour discs
Art.Nr. 457181s
(mit NLF / with ELF)*
Art.Nr. 457183s
(keine NLF / no ELF)*

Witte + Sutor GmbH – Steinberger Str. 6 – DE-71540 Murrhardt
Tel: +49 7192 9292 0 – E-Mail: info@acculux.de – Homepage: www.acculux.de

Version 2020-02

Вносител: ЮНИА-Т ЕООД, гр. Ихтиман, ул. Стипон 35, www.juniabg.com, e-mail: sales@juniabg.com