
TIP

LED | 220 V 240 V 50-60 Hz | DIMM | SDCM 3 | IP 23 | MULTI | EN 62 471 RG 0 | 100 000 L70B50


η_{ef} (lm/W) 132-143



TIP M2



TIP CW



TIP CN

LED linear fi ttings

Body:
White coated (RAL 9003) metal sheet
Optic:
CW – wide 110°
CN – narrow 60°

Application:
Surface or pendant installation
Can be installed in continuous row - fi ttings are equipped with thrue wiring 5x1,5 mm² as standard

Accessories:
ZH/UNI4 - universal 4-wires suspension (one set for 2 luminaires)
OMTIPM - protection grid TIP M, OMTIPL - protection grid TIP L

TIP MULTI	W	lm		A	B	C	X	kg
		CW	CN					
TIP6000 M1	17 • 21 • 27 • 32 • 38	2 700 • 3 300 • 4 100 • 4 800 • 5 600	2 500 • 3 100 • 3 900 • 4 600 • 5 400	1 284	145	73	1 204	3,8
TIP10000 L1	44 • 55 • 62 • 69	6 600 • 8 100 • 9 100 • 10000	6 400 • 7 900 • 8 900 • 9 800	1 584			1 504	4,8
TIP16000 L2	63 • 79 • 96 • 114	9 700 • 11 900 • 14 000 • 16100	9 500 • 11 700 • 13 800 • 15800					5

TIP	W	lm		A	B	C	X	kg
		CW	CN					
TIP6000 M1	38	5 600	5 300	1 284	145	73	1 204	3,8
TIP12000 M2	74	11 000	10 400					4
TIP8000 L1	57	8 500	8 100	1 584			1 504	4,8
TIP16000 L2	114	16 700	15 800					5

lm - luminaire light output

2200	2700	3000	4000	5700	6500	MIX	RGB	
✕	○	○	●	○	○	✕	✕	●
ON OFF	1-10V	DALI				INT	EXT	
●	✕	○	✕	✕	○	○	✕	✕

● default ○ optional ✕ not possible



OPTIC



LAMP HINGE + OM

