LYRA



... fashionable for every interior.

USE

LYRA is round LED wall and ceiling – mounted fashionable luminaire for every interior.


It is perfect solution for rezidental zones, corridors, lounges, hotels, restaurants and entrance areas.


ADVANTAGES

- Light fitting protection IP54
- Temperature resistance from ta -10 to 35 °C
- Lifetime: 50 000 hours / L80B50
- High mechanical resistence: IK10


TECHNICAL DESCRIPTION

- Light fitting protection: IP54
- Maximum ambient temperature: 35 °C
- Lifetime: 50 000 hours / L80B50
- Maximum light fitting efficiency: 113 lm/W
- CRI > 80: 4000 K
- CRI > 80: 3000 K
- Diffuser: translucent polycarbonate
- Body: polycarbonate
- Light source body: polycarbonate
- Electronic equipment: LED modules, fixed output driver





LYRA 1500



Code	Type	Max. ambient temperature [°C]	Luminous flux of light fitting [lm]	Power consumption [W]	System efficacy [lm/W]	Net weight [kg]	A [mm]	D [mm]
	For ambient temperature max. t_a = 35 °C - body: polycarbonate - diffuser: translucent polycarbonate							
41001	LYRA 1500/840	35	1670	14,8	113	0,6	200	43
41002	LYRA 1500/830	35	1540	14,8	104	0,6	200	43

ЮНИА-Т ЕООД
www.juniabg.com, e-mail: sales@juniabg.com
2050 Ихтиман, България, тел. +359 886090968