ЮНИА-Т ЕООД
www.juniabg.com, e-mail: sales@juniabg.com
2050 Ихтиман, България, тел. +359 886090968

LED Panel Long

LED 36 W 60 W

Technical information



CCT 4000K | IP41 | Ra >80 | AC 200-240V | Philips DRIVER | UGR <19

SMD4014 | CE | PF>0,95 | -40°C +50°C | 50 000h

PHILIPS

Type	Power	CCT	Lumen	Dimension	Weight
TSLX-PAN-120-36	36 W	4000 K, 6000 K	4320 lm	295 x 1195 x 11 mm	2900 g
TSLX-PAN-120-36-140	36 W	4000 K	5040 lm	295 x 1195 x 11 mm	2900 g
TSLX-PAN-150-40	40 W	4000 K, 6000 K	4800 lm	295 x 1495 x 11 mm	4250 g
TSLX-PAN-120-60	60 W	4000 K, 6000 K	7200 lm	595 x 1195 x 11 mm	6200 g
TSLX-PAN-120-60-140	60 W	4000 K	8400 lm	595 x 1195 x 11 mm	6200 g

Specifications:

IP rate: IP41
LED type: 4014 SMD LED
Driver: PHILIPS, Tsong
Beam: 120°
CTT: 4000 K , 6000 K
Luminous flux: 120 - 140 lm/W
CRI: Ra>80
Input: AC 200 - 240 V
Efficiency: >0,95
Operating temperature: -40°C to +50°C
UGR: UGR<19, UGR<21

Lifetime: 50 000 hours
Warranty: 60 months

Material: PMMA

Accessories:

Driver with emergency power supply
Philips driver
0-10V dimmable driver
Philips / XZ DALI driver

